

SKIMPLAST LP640

SKIMCOAT LIQUID PASTE

'BEST FOR CONCRETE WALLS AND CEILING'

SKIMPLAST LIQUID PASTE LP640 is a smooth skim paste rendering paste to be mixed with cement for ceilings, exterior and interior walls. It is a product for repairing surface defects in concrete or render. A smooth surface is attained by eliminating imperfections such as grooves, seams and fine cracks.

CUSTOMER BENEFITS

SKIMPLAST LIQUID PASTE offers the following advantages:

- Can be applied thinly up to 0.5mm to 4mm without flaking saving bigger cost on plastering works.
- A non toxic material resistant to ultraviolet rays and to wind-driven rain.
- No water needed
- Excellent trowelability for applicators
- Excellent white smooth finish

RECOMMENDED FOR:

- Correction of uneven concrete surfaces such as: interior and exterior walls and ceilings, formed concrete walls and pre-cast panels.
- Patching and repair of cracks, pinholes and dent gaps.
- Serves as filler to honeycomb of concrete slab, ceiling, columns and beams.

SURFACE PREPARATION

Surfaces must be structurally sound and thoroughly clean. Remove loose materials, dust, dirt, oil, laitance and other contaminants. All surfaces must be damped down with clean water just prior to application of SKIMPLAST LIQUID PASTE LP640.

APPLICATION

- Mix 1 part of SKIMPLAST LP640 with ½ to 1 part cement.
- Apply small quantities of SKIMPLAST Liquid Paste mixed with cement with stainless steel float.
- Two separate coats must be applied for a successful resurfacing (First layer as primer)
- Allow 3 hours at normal temperature between coats. Pre-covering curing time 24-48 hours.
- Allow 7 days curing

PACKAGING AND COVERAGE

25kgs / pail

FIRE AND HEALTH SAFETY

SKIMPLAST LIQUID PASTE is non toxic and non flammable.