

SKIMPLAST LP670

SKIMCOAT LIQUID PASTE

'BEST FOR CONCRETE WALLS AND CEILING'

SKIMPLAST LIQUID PASTE LP670 is a ready to use rendering paste for ceilings, exterior and interior walls. It's a ready to use product formula for repairing surface defects in concrete or render. A smooth surface is attained by eliminating imperfections such as grooves, seams and fine cracks.

CUSTOMER BENEFITS

SKIMPLAST LIQUID PASTE offers the following advantages:

- Can be applied thinly up to 0.5mm to 4mm without flaking saving bigger cost on plastering works.
- A non toxic material resistant to ultraviolet rays and to wind-driven rain.
- No water needed
- Excellent trowelability for applicators
- Excellent white smooth finish

RECOMMENDED FOR:

- Correction of uneven concrete surfaces such as: interior and exterior walls and ceilings, formed concrete walls and pre-cast panels.
- Patching and repair of cracks, pinholes and dent gaps.
- Serves as filler to honeycomb of concrete slab, ceiling, columns and beams.

SURFACE PREPARATION

Surfaces must be structurally sound and thoroughly clean. Remove loose materials, dust, dirt, oil, laitance and other contaminants. All surfaces must be damped down with clean water just prior to application of SKIMPLAST LIQUID PASTE LP670.

APPLICATION

- Apply small quantities of SKIMPLAST Liquid Paste with stainless steel float.
- Two separate coats must be applied for a successful resurfacing (First layer as primer)
- Allow 2 hours at normal temperature between coats. Pre-covering curing time 24-48 hours.

PACKAGING AND COVERAGE

25kgs / pail
1.2kg/sqm/mm (depending on porosity of concrete surface)

FIRE AND HEALTH SAFETY

SKIMPLAST LIQUID PASTE is non toxic and non flammable.