

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-8620 / BS-8620S  
LM MS Sealant**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**1. Identification of the substance/preparation and of the company/undertaking****Product name** : BS-8620 / BS-8620S LM MS Sealant**Product use** : MS sealant**Company** : Bossil Technology Sdn. Bhd.  
22A-1, Jalan Tasik Utama 10,  
The Trillium @ Lake Fields,  
Sg. Besi, 57000 Kuala Lumpur,  
Malaysia.**Telephone** : +6016 - 2119190**Fax** : -**Email** : sales@bossil.com**Website** : www.bossil.com**2. Hazard(s) identification****Substance/Mixture** : Mixture**Hazard classification** : Not classified as hazardous**Pictogram** : Not classified as hazardous**Signal word** : Not classified as hazardous**Hazard statement(s)** : Not classified as hazardous**Precautionary statement(s)** : Not classified as hazardous**Other hazards which do not result in classification but contribute to overall hazards:** None known**3. Composition/Information on ingredients**

Chemical name	CAS No.	EINECS No.	%
Limestone	1317-65-3	215-279-6	50 - 70
Diisononylphthalate	28553-12-0	249-079-5	10 - 30
Vinyltrimethoxysilane	2768-02-7	220-449-8	0.1 - 1.0
3-(2-aminoethylamino)propyltrimethoxysilane	1760-24-3	217-164-6	0.1 - 1.0
Dibutyltin bis(acetylacetonate)	22673-19-4	245-152-0	0.1 - 1.0

**4. First-aid measures****In case of inhalation:**

Remove to fresh air, keep warm and at rest. Contact physician if symptom persists.

**In case of skin contact:**

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-8620 / BS-8620S  
LM MS Sealant**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Remove contaminated clothing. Rinse with copious amount of water and soap. Get medical advice if skin irritation or a rash occurs. Wash clothing before reuse.

**In case of eye contact:**

Contact lenses should be removed. Rinse with copious amount of water immediately. Seek medical advice if eye irritation develops and persists.

**In case of ingestion:**

DO NOT induce vomiting. Rinse mouth thoroughly with water. Get medical attention if a symptom persists.

**Personal protection equipment for first-aiders:**

Pay attention to any potential hazards and use recommended personal protection equipment if potential for exposure exists.

**Most important symptoms and effects, acute and delayed:**

None known.

**5. Fire-fighting measures****Suitable extinguishing media:**

Water, alcohol-resistant foam, carbon dioxide, dry chemical.

**Unsuitable extinguishing media:**

None known.

**Specific firefighting procedures:**

Remove undamaged containers from fire area if it is safe to do so. Use extinguishing media that is suitable to local circumstances and surrounding environment.

**Special person protection equipment for firefighters:**

NIOSH-approved self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Specific hazards arising from firefighting:**

Exposure to combustion products may be a hazard to health.

**Thermal decomposition products:**

Carbon dioxide, carbon monoxide, nitrogen oxides, and other irritant gases.

**6. Accidental release measures****Personal precautions, protective equipment and emergency procedure:**

Use recommended personal protective equipment. Keep unprotected persons away. Ensure adequate ventilation.

**Measure for cleaning/collecting:**

Wipe or soak with inert liquid binding material (sand, sawdust, etc.). Scrape away cured material. Dispose the spilt material according to local or national regulations. Section 13 of this safety data sheet provides information regarding certain local or national requirements.

**Additional information:**

Prevent spillage from entering drainage/sewer systems. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

**7. Handling and storage**

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-8620 / BS-8620S  
LM MS Sealant**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**Handling:**

Ensure good ventilation during use. Avoid contact with skin and eyes. Do not eat, drink, or smoke when using the product.

**Storage:**

Ensure containers and cartridges are tightly closed. Store in a dry, well-ventilated area, and protected from direct sunlight with temperature not exceeding 30 °C. Keep away from incompatibles. Refer to section 10 for incompatible materials.

**8. Exposure controls/personal protection**

Components	CAS No.	Form of exposure (Value type)	Control Parameter	Basis
Limestone	1317-62-3	8 hours TWA (Particulate matter containing no asbestos and <1% crystalline silica)	10 mg/m <sup>3</sup>	Malaysia OSHA
Limestone (total dust)	1317-62-3	8 hours TWA	10 mg/m <sup>3</sup>	US OSHA
Limestone (respirable fraction)	1317-62-3	8 hours TWA	5 mg/m <sup>3</sup>	US OSHA
Limestone (inhalable dust)	1317-62-3	8 hours TWA	10 mg/m <sup>3</sup>	UK WEL
Limestone (respirable dust)	1317-62-3	8 hours TWA	4 mg/m <sup>3</sup>	UK WEL
Limestone	1317-62-3	8 hours TWA (Particulate matter containing no asbestos and <1% crystalline silica)	10 mg/m <sup>3</sup>	Safe Work Australia
Diisononylphthalate	28553-12-0	8 hours TWA	5 mg/m <sup>3</sup>	UK WEL

**Engineering controls:**

Product curing may form hazardous compounds. Ensure adequate ventilation and minimise workplace exposure concentrations.

**Industrial hygiene:**

Remove immediately all contaminated clothing. Do not inhale vapour. Wash hands and contaminated areas with water and soap before leaving the work site. Change clothing before leaving workplace and wash before reuse. Do not eat, drink, or smoke while using product.

**Hand protection:**

Suitable impervious protective gloves (latex, nitrile, etc.). Breakthrough time is not tested for this product. Change gloves often if possible.

**Respiratory protection:**

A NIOSH-approved respirator with filter for organic vapours is recommended where local ventilation is not adequate.

**Eye/Face protection:**

Protective goggles/safety glasses.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-8620 / BS-8620S  
LM MS Sealant**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**9. Physical and chemical properties**

<b>Appearance</b>	: Thixotropic paste
<b>Odour</b>	: Characteristic odour
<b>Odour threshold</b>	: Not determined
<b>pH</b>	: Not applicable
<b>Freezing/Melting point</b>	: Not determined
<b>Boiling point range</b>	: Not applicable
<b>Flash point</b>	: Not applicable
<b>Evaporation rate</b>	: Not applicable
<b>Flammability</b>	: Not classified as flammable
<b>Explosive properties</b>	: Not classified as explosive
<b>Oxidizing properties</b>	: Not classified as oxidizing
<b>Vapour pressure</b>	: Not applicable
<b>Vapour density</b>	: Not applicable
<b>Relative density</b>	: Approximately 1.55
<b>Solubility in water</b>	: Not determined
<b>N-octanol/water partition coefficient</b>	: Not determined
<b>Decomposition temperature</b>	: Not determined
<b>Viscosity</b>	: Not applicable

**10. Stability and reactivity****Reactivity:**

No reactive hazards known.

**Stability:**

Stable under recommended handling and storage conditions.

**Conditions to avoid:**

Exposure to water/water vapour and humid air.

**Hazardous reactions:**

Hazardous polymerization will not occur.

**Hazardous decomposition products:**

None known.

**Incompatible materials:**

Water, alcohol, and amines.

**11. Toxicology information**

No specific oral, inhalation or dermal toxicology data is known for this product. Any toxicological data included in this section is based on the data associated with the components.

**Acute oral toxicity, LD<sub>50</sub> (rat):**

Not classified based on available information and/or concentration of components.

Limestone

&gt;2,000 mg/kg

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-8620 / BS-8620S  
LM MS Sealant**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Diisononylphthalate	>10,000 mg/kg
Vinyltrimethoxysilane	7,120 mg/kg
3-(2-aminoethylamino)propylmethoxysilane	2,295 mg/kg
Dibutyltin bis(acetylacetonate)	1,864 mg/kg

**Acute dermal toxicity, LD<sub>50</sub> (rabbit):**

Not classified based on available information and/or concentration of components.

Diisononylphthalate	>3,160 mg/kg
Vinyltrimethoxysilane	3,460 mg/kg
3-(2-aminoethylamino)propylmethoxysilane	2,000 mg/kg
Dibutyltin bis(acetylacetonate)	>2,000 mg/kg

**Acute inhalation toxicity, LC<sub>50</sub> (4 hours, rat):**

Not classified based on available information and/or concentration of components.

Diisononylphthalate	>4.4 mg/L (aerosol)
3-(2-aminoethylamino)propyltrimethoxysilane	>1.49 mg/L (mist)
Vinyltrimethoxysilane	2,773 ppm

**Serious eye damage/eye irritation:**

Not classified based on available information and/or concentration of components.

Limestone	Not eye irritant.
Diisononylphthalate	Not eye irritant.
Vinyltrimethoxysilane	Not eye irritant.
3-(2-aminoethylamino)propylmethoxysilane	Irreversible effects on the eye.
Dibutyltin bis(acetylacetonate)	Causes eye irritation.

**Skin corrosion/skin irritation:**

Not classified based on available information and/or concentration of components.

Limestone	Not skin irritant.
Diisononylphthalate	Very mild skin irritant

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-8620 / BS-8620S  
LM MS Sealant**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Vinyltrimethoxysilane	Not skin irritant.
3-(2-aminoethylamino)propylmethoxysilane	Not skin irritant.
Dibutyltin bis(acetylacetonate)	Causes skin irritation.

**Respiratory/Skin sensitisation:**

Not classified based on available information and/or concentration of components.

Limestone	Not sensitising on skin.
Diisononylphthalate	Not sensitising to respiratory and skin.
Vinyltrimethoxysilane	Not sensitising on skin.
3-(2-aminoethylamino)propylmethoxysilane	Probability or evidence of skin sensitisation in humans.
Dibutyltin bis(acetylacetonate)	Sensitising on skin.

**Germ cell mutagenicity:**

Not classified based on available information and/or concentration of components.

Limestone	Negative genotoxicity <i>in vitro</i> .
Diisononylphthalate	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .
Vinyltrimethoxysilane	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .
Dibutyltin bis(acetylacetonate)	Negative genotoxicity <i>in vitro</i> . Negative genotoxicity <i>in vivo</i> .

**Carcinogenicity:**

Not classified based on available information and/or concentration of components.

Diisononylphthalate	Negative carcinogenicity. NOAEL: 88.3 mg/kg bw/day
Dibutyltin bis(acetylacetonate)	No statistically significant increase in tumour incidences. NOAEL: 152 ppm

**Reproductive toxicity:**

Not classified based on available information and/or concentration of components.

Limestone	No effect on fertility and foetal development.
Diisononylphthalate	No effect on fertility and foetal development.
Vinyltrimethoxysilane	No effect on fertility and foetal development.
3-(2-aminoethylamino)propylmethoxysilane	No effect on fertility and foetal development.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-8620 / BS-8620S  
LM MS Sealant**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Dibutyltin bis(acetylacetonate)	No data on fertility. No effect on foetal development.
---------------------------------	---

**Specific target organ toxicity – single exposure:**

Not classified based on available information and/or concentration of components.

3-(2-aminoethylamino)propylmethoxysilane	Exposure by ingestion. No significant health effect at concentration of 100 mg/kg body weight or less.
--	---

**Specific target organ toxicity – repeated exposure:**

Not classified based on available information and/or concentration of components.

Limestone	Exposure for 6 weeks by ingestion on rats. NOAEL: 1,000 mg/kg
Diisononylphthalate	Exposure for 104 weeks by ingestion on rats. NOAEL: 88.3 mg/kg bw/day
	Exposure by inhalation on rats. NOAEC: 500 mg/m <sup>3</sup>
	Exposure for 6 weeks by dermal on rabbits. NOAEL: 500 mg/kg bw/day
Vinyltrimethoxysilane	Exposure by ingestion for 43 days on rats. NOAEL: <62.5 mg/kg bw/day LOAEL: 62.5 mg/kg bw/day
	Exposure by inhalation for 14 days on rats. NOAEL: 10 ppm LOAEL: 100 ppm
3-(2-aminoethylamino)propylmethoxysilane	Exposure by ingestion for 28 days on rats. NOAEL: 500 mg/kg bw/day
	Exposure by dermal for 11 days on rats. NOAEL: 1,545 mg/kg bw/day
Dibutyltin bis(acetylacetonate)	Exposure by ingestion for 2 weeks on rats. NOAEL: <50 ppm LOAEL: 50 ppm

**Aspiration toxicity:**

Not classified based on available information and/or concentration of components.

**Likely route of administration:**

Inhalation, skin contact, and ingestion.

**12. Ecological information**

Individual components of this mixture have been independently tested by the raw material suppliers and any known results have been presented below. The results for the individual components may not be representative of the ecological toxicity of this finished product. This finished product has not been tested to determine individual toxicological/ecological limits.

**Ecology toxicity:**

No adverse effect on aquatic organisms is predicted based on available information and/or concentration of components.

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-8620 / BS-8620S  
LM MS Sealant**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

Limestone Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC <sub>50</sub> : >100 mg/L Exposure for 48 hours, EC <sub>50</sub> : >100 mg/L Exposure for 72 hours, EC <sub>50</sub> : >14 mg/L
Diisononylphthalate Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC <sub>50</sub> : >102 mg/L Exposure for 48 hours, EC <sub>50</sub> : >74 mg/L Exposure for 72 hours, EC <sub>50</sub> : >88 mg/L
Vinyltrimethoxysilane Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC <sub>50</sub> : 191 mg/L Exposure for 48 hours, EC <sub>50</sub> : 168.7 mg/L Exposure for 7 days, EC <sub>50</sub> : 210 mg/L
3-(2-aminoethylamino)propylmethoxysilane Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC <sub>50</sub> : 597 mg/L Exposure for 48 hours, EC <sub>50</sub> : 81 mg/L Exposure for 72 hours, EC <sub>50</sub> : 8.8 mg/L
Dibutyltin bis(acetylacetonate) Toxicity to fish Toxicity to crustacean Toxicity to algae or other aquatic plants	Exposure for 96 hours, LC <sub>50</sub> : >2 mg/L Exposure for 48 hours, EC <sub>50</sub> : 0.0036 mg/L Exposure for 72 hours, EC <sub>50</sub> : >2 mg/L

**Persistence and degradability:**

Not likely to be persistent based on available information and/or concentration of components.

Diisononylphthalate	Readily biodegradable. Exposure for 28 days, 81% biodegradation.
3-(2-aminoethylamino)propylmethoxysilane	Not readily biodegradable. 39% biodegradation. 0.025 hours half-life degradation.
Vinyltrimethoxysilane	Not readily biodegradable. Exposure for 28 days, 51% biodegradation.

**Bioaccumulative potential:**

No bioaccumulation potential based on available information and/or concentration of components.

Diisononylphthalate	BCF: <3
3-(2-aminoethylamino)propylmethoxysilane	Log K <sub>ow</sub> : -0.3

**Mobility in soil:**

No data available.

**13. Disposal information****Waste treatment/disposal methods - unused products**

Waste disposal must be in compliance with environmental protection requirements and local regulations.

**Waste treatment/disposal methods - contaminated packaging**

Dispose of as unused product. Empty container should be taken to an approved waste handling site for recycling or disposal.



**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-8620 / BS-8620S  
LM MS Sealant**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**14. Transport information****Road transport (UNRTDG)** : Not regulated as dangerous goods.**UN number** : Not applicable**Proper shipping name** : Not applicable**Technical name** : Not applicable**Hazard class** : Not applicable**Classification code** : Not applicable**Packing group** : Not applicable**Marine transport (IMDG)** : Not regulated as dangerous goods.**UN number** : Not applicable**Proper shipping name** : Not applicable**Technical name** : Not applicable**Hazard class** : Not applicable**EmS** : Not applicable**Packing group** : Not applicable**Marine pollutant** : Not applicable**Air transport (IATA)** : Not regulated as dangerous goods.**UN number** : Not applicable**Proper shipping name** : Not applicable**Technical name** : Not applicable**Hazard class** : Not applicable**Packing group** : Not applicable**15. Regulatory information****Safety, health, and environmental regulations specific for the hazardous chemical in question:**

Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations 2010 (Malaysia)

Occupational Safety and Health (Classification, Labelling, and Safety Data Sheet of Hazardous Chemicals) Regulations 2013 (Malaysia)

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (European Union)

Occupational Safety and Health Administration (OSHA) (2006) Air Contaminants. 29 CFR 1910.1000 (United States of America)

Work Health and Safety Act 2011 (Australia)

EH40/2005 Workplace exposure limits (United Kingdom)

**Chemical inventory status:**

Australia AICS : All ingredients listed or exempt.

Canada DSL : All ingredients listed or exempt.

Japan ENCS : All ingredients listed or exempt.

Korea KECI : All ingredients listed or exempt.

Taiwan ECSN : All ingredients listed or exempt.

**16. Other information**

**BOSSIL TECHNOLOGY SDN. BHD.****Safety Data Sheet****BS-8620 / BS-8620S  
LM MS Sealant**

Issued date: 22/12/16

Revision date: -

Revision No.: 0

**Definitions:**

<b>TWA</b>	: Time-weighted average.
<b>STEL</b>	: Short-term exposure level.
<b>OSHA</b>	: Occupational Safe and Health Act
<b>WEL</b>	: Workplace exposure limits
<b>LD<sub>50</sub></b>	: The minimum dose required for lethal effects in 50% of a given population of test specimens.
<b>ppm</b>	: part per million
<b>bw</b>	: body weight
<b>BCF</b>	: Bioconcentration factor
<b>NOAEL</b>	: No-observed-adverse-effect-level
<b>LOAEL</b>	: Lowest-observed-adverse-effect level
<b>NIOSH</b>	: National Institute for Occupational Safety and Health.
<b>UNRTDG</b>	: United Nations Recommendations on the Transport of Dangerous Goods
<b>IMDG</b>	: International Maritime Dangerous Goods
<b>IATA</b>	: International Air Transport Association
<b>AICS</b>	: Australian Inventory of Chemical Substances
<b>DSL</b>	: Domestic Substance List
<b>ENCS</b>	: Existing and New Chemical Substances.
<b>KECI</b>	: Korea Existing Chemicals Inventory.
<b>ECSN</b>	: Existing Chemical Substance Nomination.

All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist. The details contained herein are based on our present state of knowledge and experience in characterising our product with regard to any possible safety requirement at the date of its publication. We do, however, pass them on without any warranty or property assurances.