

BITUPRIME 1000

PRODUCT DESCRIPTION

BITUPRIME 1000 Bitumen solvent primer is a combination of oil bitumen and a specially selected organic solvent to form a bitumen primer that being use as a sealer prior to the application of bitumen membrane. The product has a short drying time and ability to penetrate on concrete substrates.

AREA OF APPLICATION

BITUPRIME 1000 Bitumen Solvent Primer is used for preparing (priming) of the substrates (concrete slab, cement-sand screed, etc.) before waterproofing with Torch on Membrane or Self-Adhesive membrane.
Primer Consumption – 0.3kg/m².

| INDICATOR NAME | UNIT | VALUE | TEST METHOD |
|-----------------------------|------|-----------|-------------|
| Density | g/cc | 0.85-0.88 | ASTM D 70 |
| Penetration at | 25°C | 2-50 dmm | ASTM D5 |
| Say bolt Fural Viscosity at | 25°C | 25-1 25 | ASTM D 88 |

PERFORMANCE OF WORKS

Temperature ranges from -10°C to +40°C. At temperature below +5°C withstand mastic in warm room for at least 24 hours. Drying time under standard conditions is not more than 12 hours.

Do not use near open flame. Work in well-ventilated areas. Avoid contact with skin and eyes.

STORAGE

Keep in a dry place, away from the sun light at temperature from -20°C to +30°C. Guaranteed shell life: 18 months

PACKAGING INFORMATION

Metal pails 16 liters net content

NOTE: The information and in particular, recommendations relating to the application and end-use of Sealbond products, are given in good faith based on Sealbond's best knowledge and specialty on construction chemical formulations. Products are properly stored and handled in accordance with Sealbond's endorsements. Hence, subject to the care and method of application, deviations (from published values) in performance may occur. In practice, to different materials used, as well as varying working conditions and environments beyond our control Sealbond Chemical Industries Inc. strictly recommend carrying out intensive trials to test the suitability of the product with regards to the required processes and applications. Therefore, any liability for such recommendations or any oral/verbal advice is expressly excluded unless we have acted wilfully or by gross negligence. Sealbond Chemicals Industries Inc. is not liable for installation or faulty installation. It is always the responsibility of the installer/applicator/purchaser to guarantee and certify the installation of materials.

All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the Product Data Sheet for the product awareness, copies of which will be supplied on request and is free of charge.

DISTRIBUTED BY:



SEALBOND CHEMICAL INDUSTRIES INC.

A2 Araneta St. Gen. Natividad St. Ibayo Tipas, Taguig City, Philippines
Tel. No.: (632) 881-8813 / 239-5609 / 239-9332 / 844-9311 Telefax: 239-9332
Email: info@sealbondchemicals.com Website: www.sealbondchemicals.com